

CRL Double Roller Track System

new

- Perfect for Showcases and Display Cabinets
- Designed for 1/4" (6 mm) Tempered Glass
- Smooth Operating Nylon Rollers are Built Into the Lower Track
- Simple 'Lift and Drop' Glass Installation
- Top Channel Can Be Used as Side Jamb or for a Surround Frame
- Polished Aluminum Finish



Our new Double Roller Track System is beautifully designed to be both attractive and functional. Everything you need to install sliding glass doors into a showcase or cabinet is included. Just cut the Upper Channel and Lower Track to size and it's ready to install.

Smooth operating nylon rollers are spaced every 4" (102 mm) in the Lower Track, which has been pre-drilled with holes for securing it to the base. The Top Channel is easily set into place above the Bottom Track, and can even be used as a side jamb to provide a full surround frame for the glass doors.

NOTE: Designed for use with 1/4" (6 mm) tempered glass, the maximum recommended panel size is 60" (1524 mm) tall by 30" (792 mm) wide, or a ratio of 1.5:1. Recommended minimum overlap of glass panels is 1-1/2" (38 mm).

General Glass Cutting Guidelines:

Glass Height = Opening Height minus 7/8" (22 mm).



TOP CHANNEL

CAT. NO.	LENGTH	FINISH
16190	78" (2 m)	Polished Aluminum
16195	157" (4 m)	Polished Aluminum

Minimum order: 1 stock length. All track assemblies can be combined for quantity pricing. A Packing Charge will be added to orders of fewer than four combined lengths. 157" (4 m) lengths must ship common carrier, unless you specify we cut them for U.P.S. A Cutting Charge will apply.



LOWER TRACK WITH NYLON ROLLERS

CAT. NO.	LENGTH	FINISH
16180	78" (2 m)	Polished Aluminum

Minimum order: 1 stock length. All track assemblies can be combined for quantity pricing. A Packing Charge will be added to orders of fewer than four combined lengths. 157" (4 m) lengths must ship common carrier, unless you specify we cut them for U.P.S. A Cutting Charge will apply.

